

SST-ST1500

Powersupply for Pedestal/4U Servers

SPECIFICATION

ModelName
→ SST-ST1500

Size
→ Ps2

InputVoltage
→ 110V-240V

Connectors

MotherBoardConnector	20+4Pins	-1			
CoreVoltageConnector	4+4Pins	-1			
CoreVoltageConnector	8Pins	-1			
			Opt1	Opt2	Opt3
PCIExpress Connector	6+2Pins-	4	4	4	4
PCIExpress Connector	6Pins	- 4	4	4	4
SATAPowerConnector		- 6	12	0	0
4PinPowerConnector		- 6	0	12	12
→ FDDPowerConnector		- 2	0	0	2

Ampere Rating

Voltage	Amperage	
+3.3V	- 40.0A	} Max.200W
+5V	- 40.0A	
+12V1	- 25.0A	} Max.1320W
+12V2	- 25.0A	
+12V3	- 25.0A	
→ +12V4	- 25.0A	
+12V5	- 25.0A	
+12V6	- 25.0A	
+12V7	- 25.0A	
+12V8	- 25.0A	
-12	- 0.5A	
+5VSB	- 6.0A	

TotalOutput
→ 1500W

RecommendedChasis

→ SR-108
RM-413
RM-4201
RM-4241
SST-GD098



SST-ST-1500



PRIME
SOURCE

PrimeSourceTechnologiesPvt.Ltd.

www.primesource.in