

# FSP850-50FGPH3

## Server Powersupply

### Specification

**Model Name** FSP850-50FGPH3

**Size** 1U Single / Flex ATX

**Input Voltage** 100 V - 240 V

<b>Connectors</b>		<b>Opt1</b>	<b>Opt2</b>
Mother Board Connector 24 Pins	-	1	1
Core Voltage Connector 8 Pins	-	1	1
Core Voltage Connector 4+4 Pins	-	1	1
PCI Express Connector 6+2 Pins	-	1	1
PCI Express Connector 6 Pins	-	1	1
SATA Power Connector	-	4	2
4 Pin Power Connector	-	4	2
FDD Power Connector	-	1	1

<b>Ampere Rating</b>		<b>Voltage</b>	<b>Amperage</b>	
	-	+3.3 V	25.0A	} Max. 100W
	-	+5 V	25.0A	
	-	+12 V	70.0A	
	-	-12 V	0.5A	
	-	+5 VSB	3.0A	

**Total Output** 850 W

<b>Compatible Chassis</b>		
RM-1004		RM-2081
RM-1021		RM-2081A
RM-13310		RM-2081B
RM-13604		RM-2082AH
RM-1042		RM-2082AN
RM-1044		RM-2142A
RM-1044B		RM-23808
RM-238A		RM-23524
RM-2003		RM-3001



**Prime Source Technologies Pvt. Ltd**

[www.primesource.in](http://www.primesource.in)